

# Biometra TRIO PCR Thermal Cycler



## General

- Stand-alone control by 7" color touchscreen or remote control by cycler network
- Whisper Quiet with max. 45 dB
- Small footprint and minimal clearance zone
- Three different sample blocks for various sample volumes, with three independently working blocks each
- HPSL technology for ideal constant contact pressure independent of the used consumable
- Suitable for low-profile and high-profile plastic with or without skirt, as well for semi-skirt

## Thermal block

	3 x 48	3 x 30	3 x Combi
Sample block	Aluminum, special alloy	Aluminum, special alloy	Aluminum, special alloy
Block capacity	3 x 48 x 0.1/0.2 mL tubes, 3 x 6 x 8-Well strips, 3 x 48 well micro plate	3 x 30 x 0.5 mL tubes	3 x 48 x 0.1/0.2 mL tubes, 3 x 6 x 8 well strips, 3 x 48 well micro plate, 3 x 18 <sup>3</sup> x 0.5 mL tubes
Proposed sample volume	5 - 70 µL	20 - 200 µL	5 - 70 µL (0.2 mL) 20 - 140 µL (0.5 mL)
Max. heating <sup>1</sup>	5.0 °C/s	4.0 °C/s	3.0 °C/s
Average heating <sup>1</sup>	4.5 °C/s	3.6 °C/s	2.7 °C/s
Max. cooling <sup>1</sup>	4.2 °C/s	3.6 °C/s	2.7 °C/s
Average cooling <sup>1</sup>	3.8 °C/s	3.2 °C/s	2.4 °C/s
Block temperature uniformity <sup>2</sup> at target temperature			
95 °C	± 0.60 °C	± 0.60 °C	± 0.60 °C
70 °C	± 0.30 °C	± 0.30 °C	± 0.30 °C
55 °C	± 0.20 °C	± 0.20 °C	± 0.20 °C
Temperature optimization	Temperature Optimization Step (TOS)	Temperature Optimization Step (TOS)	Temperature Optimization Step (TOS)

<sup>1</sup> measured at cavity wall of the block

<sup>2</sup> typical value after 15 sec

<sup>3</sup> The capacity is increased to 35 x 0.5 ml tubes for tubes with small caps.

Block exchange	No
----------------	----

## Technical Data

### Biometra TRIO

Number of blocks	3
Tempering method	Peltier elements
Standby temperature	Yes, down to 4 °C
Temperature control mode	Block control
Adjustable temperature range	3 °C to 99 °C
Temperature control accuracy	± 0.1 °C

## Heated lid

Heated lid	High-Precision Smart Lid (HPSL)
Lid temperature	30 °C to 110 °C
Contact pressure	Approx. 6 kg, manual with integrated slip clutch for constant contact pressure independent from the used consumables

## Control

Control	Stand-alone or remote control via optional Windows software Biometra TSuite
Control and analysis software	Optional & licensed: Biometra TSuite thermal cycler management software
Min. requirement PC	Windows 10
Minimum requirement cyler	Firmware version ME 2.04 – RE 2.04
Language	English, German, Chinese
Display	7" Color touchscreen
Export function	Yes
Power fail function	Yes
Quick start function	User-specific quick start
Time inc	1 to 240 s/cycle
Temperature inc/dec	±0.1 to 20 °C/cycle
Memory capacity	At least 350 programs with a typical 6 step program, in up to 90 user directories
Features	<ul style="list-style-type: none"><li>▪ Extended Self Test</li><li>▪ Graphical or spreadsheet programming</li><li>▪ Multip-step programming</li><li>▪ Incubation mode</li><li>▪ Protocol templates</li><li>▪ Program preview</li></ul>

## Dimensions

## Technical Data

### Biometra TRIO

Weight netto	Approx. 17.3 kg
Dimensions (W x D x H)	300 mm x 410 mm x 250 mm
Required clearance zone	10 cm behind rear side of the device. When operating several units side by side, an additional 10 cm between the units.

### Additional technical data

Interface	<ul style="list-style-type: none"><li>■ USB-A (front side): connection of an USB flash drive</li><li>■ Ethernet (back side): connection to a network</li></ul>
Fuses	2x T 10A H 250 V
Power supply	100 V, 115 V oder 230 V $\pm$ 10 %, 50 – 60 Hz
Power consumption	
Active power	Max. 800 W
Apparent power	Max. 1000 VA
Noise emission	Max. 45 dBA
Operation conditions	15 °C to 35 °C, max. 70 % humidity, max. 2.000 m NN. Operation > 2000 m above sea level has not been tested according to standards. Practical experience with operation > 2000 m has shown normal operating behavior, as is to be expected due to the design and components used. It is possible that heating and cooling rates are reduced due to the low air density. This is not a device fault. The heating and cooling rates are automatically adjusted to the conditions. Overvoltage category II, pollution degree 2, IP20
Warranty	2 years warranty o the device system

This document is true and correct at the time of publication; the information within is subject to change. Other documents may supersede this document, including technical modifications and corrections.

Content may be used without written permission but with citation of source. © Analytik Jena AG